



Basic features

Approval/Conformity	CE EAC cULus WEEE
---------------------	----------------------------

Electrical connection

Cable diameter D	3.00 mm
Cable length L	2 m
Connection type	Cable, 2.00 m, PVC
Number of conductors	3

Electrical data

No-load current I_0 max., damped	7 mA
No-load current I_0 max., undamped	2 mA
Operating voltage U_b	10...30 VDC
Output resistance R_a	33.0 kOhm
Protection class	II
Rated insulation voltage U_i	250 V AC
Ready delay t_v max.	25 ms
Residual current I_r max.	10 μ A
Ripple max. (% of U_e)	10 %
Switching frequency	5000 Hz

Environmental conditions

Ambient temperature	-25...70 °C
Protection degree	IP68

Functional safety

MTTF (40 °C)	595 a
--------------	-------

Material

Housing material	Brass
Material jacket	PVC
Material sensing surface	PBT
Surface protection	Nickel-free coated

Mechanical data

Dimension	$\varnothing 8 \times 50$ mm
Installation	for flush mounting
Size	M8x1

Output/Interface

Switching output	PNP normally open (NO)
------------------	------------------------

Range/Distance

Assured operating distance S_a	1.6 mm
Rated operating distance S_n	2 mm
Real switching distance s_r	2 mm

Remarks

The sensor is functional again after the overload has been eliminated.
For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Wiring Diagrams

