



### Basic features

Approval/Conformity	CE cULus EAC WEEE
Basic standard	IEC 60947-5-2

### Display/Operation

Function indicator	yes
Power indicator	no

### Electrical connection

Cable diameter D	4.60 mm
Cable length L	3 m
Conductor cross-section	0.34 mm <sup>2</sup>
Connection type	Cable, 3.00 m, PVC
Number of conductors	2
Polarity reversal protected	yes
Protection against device mix-ups	no
Short-circuit protection	yes

### Electrical data

Min. operating current $I_m$	5 mA
Operating voltage $U_b$	20...250 VDC/20...250 VAC
Protection class	II
Rated insulation voltage $U_i$	250 V AC
Rated operating current $I_e$	130 mA
Rated operating voltage $U_e$ AC	110 V
Rated short circuit current	100 A
Ready delay $t_v$ max.	100 ms
Residual current $I_r$ max.	1700 $\mu$ A
Switching frequency	1000 Hz
Utilization category	AC-140 DC -13
Voltage drop static max.	11 V

### Environmental conditions

Ambient temperature	-25...70 °C
Contamination scale	3
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
Protection degree	IP67

### Material

Housing material	Stainless steel
Material jacket	PVC
Material sensing surface	PA 12

## Mechanical data

Dimension	Ø 12 x 60 mm
Installation	for flush mounting
Size	M12x1
Tightening torque	20 Nm

## Output/Interface

Switching output	Normally closed (NC)
------------------	----------------------

## Range/Distance

Assured operating distance $S_a$	1.6 mm
Hysteresis H max. (% of $S_r$ )	15.0 %
Rated operating distance $S_n$	2 mm
Real switching distance $s_r$	2 mm
Repeat accuracy max. (% of $S_r$ )	5.0 %
Temperature drift max. (% of $S_r$ )	10 %
Tolerance $S_r$	±10 %

## Remarks

$T_a \geq 25 \text{ °C} \dots \leq 70 \text{ °C}$ :  $I_e = 130 - 0.67 \times (T_a - 25)$

Once the overload has been eliminated, interrupt operating voltage  $V_s$  for approx. 2 sec.

## Wiring Diagrams

