



Basic features

Approval/Conformity	CE IECEX ATEX WEEE
Basic standard	EN 60079-0 EN 60079-11 IEC 60947-5-6
Ex marking	ATEX: Ex II 1G Ex ia IIC T6 Ga Ex II 1D Ex ia IIIC T65 °C Da IECEX: Ex ia IIC T6 Ga Ex ia IIIC T65 °C Da

Display/Operation

Power indicator	no
-----------------	----

Electrical connection

Conductor cross-section	0.34 mm ²
Connection type	Cable, FEP
Polarity reversal protected	no
Short-circuit protection	no

Electrical data

Current consumption max., damped	1 mA
Operating voltage U _b	7.7...9 VDC
Rated insulation voltage U _i	12.6 V DC
Rated operating voltage U _e DC	8.2 V
Rated series resistance R _v	1000 Ohm

Environmental conditions

Ambient temperature	-20...60 °C, depending on Ex category
EN 60068-2-27, Shock	Half-sinus, 30 gn, 11 ms
EN 60068-2-6, Vibration	55 Hz, amplitude 1 mm, 3x30 min
Protection degree	IP68

Functional safety

MTTF (40 °C)	4110 a
--------------	--------

Material

Housing material	Stainless steel
Material jacket	FEP
Material sensing surface	PTFE

Mechanical data

Dimension	Ø 30 x 77 mm
Installation	non-flush
Size	M30x1.5
Tightening torque	40 Nm

Output/Interface

Interface	NAMUR
-----------	-------

Range/Distance

Rated operating distance S _n	15 mm
Repeat accuracy max. (% of S _r)	5.0 %
Temperature drift max. (% of S _r)	10 %
Tolerance S _r	±10 %

Wiring Diagrams

