

1) Optical axis receiver, 2) Optical axis emitter, 3) Operating voltage, 4) Light reception/limit area, 5) Sn



### Basic features

<b>Approval/Conformity</b>	cULus CE EAC WEEE
<b>Basic standard</b>	IEC 60947-5-2
<b>Principle of operation</b>	Photoelectric sensor
<b>Reference reflector</b>	BOS R-1
<b>Scope of delivery</b>	2x nut M18x1 User manual
<b>Series</b>	18M
<b>Style</b>	Cylinder Straight optics

### Electrical data

<b>Load capacitance max. at Ue</b>	0.2 µF
<b>No-load current I<sub>o</sub> max. at Ue</b>	50 mA
<b>Operating voltage U<sub>b</sub></b>	10...30 VDC
<b>Protection class</b>	II
<b>Rated insulation voltage U<sub>i</sub></b>	75 V DC
<b>Rated operating current I<sub>e</sub></b>	100 mA
<b>Rated operating voltage U<sub>e</sub> DC</b>	24 V
<b>Ready delay t<sub>v</sub> max.</b>	20 ms
<b>Residual current I<sub>r</sub> max.</b>	30 µA
<b>Ripple max. (% of U<sub>e</sub>)</b>	15 %
<b>Switching frequency</b>	800 Hz
<b>Turn-off delay t<sub>off</sub> max.</b>	0.63 ms
<b>Turn-on delay t<sub>on</sub> max.</b>	0.63 ms
<b>Utilization category</b>	DC -13
<b>Voltage drop U<sub>d</sub> max. at I<sub>e</sub></b>	2.5 V

### Display/Operation

<b>Adjuster</b>	1-turn potentiometer
<b>Display</b>	LED green: Power Error - LED green, flashing LED yellow: Light received Limit range - LED yellow, flashing
<b>Setting</b>	Sensitivity (Sn)

### Electrical connection

<b>Connection</b>	Connector, M12x1-Male, 4-pin
<b>Contact, surface protection</b>	Gold plated
<b>Polarity reversal protected</b>	yes
<b>Protection against device mix-ups</b>	yes
<b>Short-circuit protection</b>	yes

### Environmental conditions

<b>Ambient temperature</b>	-5...55 °C
<b>Contamination scale</b>	3
<b>EN 60068-2-27, Shock</b>	Half-sinus, 30 gn, 11 ms, 3x6 Half-sinus, 100 gn, 2 ms, 3x8000
<b>EN 60068-2-6, Vibration</b>	10...55 Hz, amplitude 1 mm, 3x30 min 10...2000 Hz, amplitude 1 mm, 30 gn, 3x5 h
<b>Protection degree</b>	IP67

## Functional safety

MTTF (40 °C) 872 a

## Material

Housing material Brass  
 Housing material, surface protection nickel plated  
 Material sensing surface Glass, anti-glare  
 Surface protection nickel plated

## Mechanical data

Dimension Ø 18 x 75 mm  
 Mounting Nut M18x1  
 Tightening torque max. 15 Nm  
 30 Nm

## Optical features

Ambient light max. 10000 Lux  
 Beam characteristic Divergent  
 LED group per IEC 62471 Exempt Group  
 Light spot size Ø 300 mm at 7 m  
 Light type LED infrared  
 Polarizing filter no  
 Principle of optical operation Retroreflective sensor  
 Switching function, optical Light-on  
 dark-on  
 Wave length 850 nm

## Output/Interface

Switching output PNP normally open (NO)  
 PNP NC Pins 4-2

## Range/Distance

Range 0...10 m  
 Rated operating distance Sn 10 m Adjustable

## Remarks


The sensor is functional again after the overload has been eliminated.  
 For additional information, refer to user's guide.  
 Order accessories separately.  
 For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

## Connector Drawings



## Wiring Diagrams



## Opto Symbols

