

1) Display and control panel, 2) Process connection, 3) Housing rotatable 320°



## Basic features

Approval/Conformity	CE cULus WEEE
Operating panel	2 buttons 320° rotation 4-digit, 7-segment display, red

## Display/Operation

Switching function display	LED
----------------------------	-----

## Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Short-circuit protection	yes

## Electrical data

Current draw max.	50 mA
Load cycles	100 million
Operating voltage Ub	18...36 VDC
Output current max.	500 mA
Protection class	III
Switching cycles min.	100 million
Switching frequency	200 Hz

## Environmental conditions

Ambient temperature	-25...85 °C
Compensation temperature	-25...85 °C
EN 60068-2-27, Shock	30 g, 11 ms
EN 60068-2-6, Vibration	30 g, 10...2000 Hz
Interference immunity	EN 61000-6-2: 2005
Media temperature	-25...125 °C
Noise emission	EN 61000-6-4:2013
Protection degree	IP67
Storage temperature	-40...85 °C
Temperature coefficient typ.	≤ ±0.3 % FSO/10K

## Functional safety

MTTF (40 °C)	368 a
--------------	-------

## Material

Connector housing, material	Stainless steel (1.4307)
Gasket, material	Fluoroelastomer
Housing material	PA PA 6.6
Measuring cell, material	Ceramic Al <sub>2</sub> O <sub>3</sub>
Process connection material	Stainless steel (1.4301)

## Mechanical data

Process connection	G 1/4" (DIN 3852)
Tightening torque max.	5 Nm
Weight	230.00 g

## Output/Interface

<b>Analog output</b>	Analog, current 4...20 mA
<b>Switching output</b>	PNP normally open/normally closed (NO/NC)

## Range/Distance


<b>Accuracy</b>	±0.5 % FSO BFSL
<b>Burst pressure</b>	15.00 bar
<b>Long-term stability max.</b>	0.3 % FSO/year
<b>Measuring range</b>	0...5 bar
<b>Overload pressure</b>	10 bar
<b>Repeat accuracy</b>	≤ ± 0.2 % FSO
<b>Resolution</b>	≤ 12 bits
<b>Sampling rate</b>	1 ms

## Remarks

vacuum-tight  
 Permissible burden on analog output  $R_{max} = 330 \text{ Ohm}$   
 For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

## Connector Drawings



## Wiring Diagrams

