

1) Display and control panel, 2) Process connection, 3) Housing rotatable 320°



Basic features

Approval/Conformity	CE cULus WEEE
Operating panel	2 buttons 320° rotation 4-digit, 7-segment display, red

Display/Operation

Switching function display	LED
-----------------------------------	-----

Electrical connection

Connection	M12x1-Male, 4-pin, A-coded
Polarity reversal protected	yes
Short-circuit protection	yes

Electrical data

Current draw max.	50 mA
Load cycles	100 million
Operating voltage U_b	18...36 VDC
Output current max.	250 mA
Protection class	III
Switching cycles min.	100 million
Switching frequency	200 Hz

Environmental conditions

Ambient temperature	-25...85 °C
Compensation temperature	-25...85 °C
Interference immunity	EN 61326-2-3: 2006
Media temperature	-25...125 °C
Noise emission	EN 61326-2-3:2007
Protection degree	IP67
Storage temperature	-40...85 °C
Temperature coefficient typ.	≤ ±0.3 % FSO/10K

Functional safety

MTTF (40 °C)	386 a
---------------------	-------

Material

Connector housing, material	Stainless steel (1.4307)
Gasket, material	Fluoroelastomer
Housing material	PA PA 6.6
Measuring cell, material	Ceramic Al ₂ O ₃
Process connection material	Stainless steel (1.4301)

Mechanical data

Process connection	G 1/4" (DIN 3852)
Tightening torque max.	5 Nm
Weight	230.00 g

Output/Interface

Interface	IO-Link 1.1
Switching output	2x PNP normally open/normally closed (NO/NC)

Range/Distance

Accuracy	±0.5 % FSO BFSL
Burst pressure	1000.00 bar
Long-term stability max.	0.3 % FSO/year
Measuring range	0...400 bar
Overload pressure	650 bar
Repeat accuracy	≤ ± 0.2 % FSO
Resolution	≤ 12 bits
Sampling rate	1 ms


Remarks

vacuum-tight


For more information about MTTF and B10d see MTTF / B10d Certificate

Indication of the MTTF- / B10d value does not represent a binding composition and/or life expectancy assurance; these are simply experiential values with no warranty implications. These declared values also do not extend the expiration period for defect claims or affect it in any way.

Connector Drawings




Wiring Diagrams



1)

1) Standard mode



2)

2) IO-Link mode