



PRODUCT DETAILS – 131B3319 / EAN: 5702427174894

VLT® HVAC DRIVE FC 102

FC-102P15KT4P55H1XGXXXXSXXXXAXBXCXXXXDX

Danfoss VLT® HVAC Drive FC-102 Drive is dedicated to ventilation, heating, and refrigeration applications. With a wide range of powerful standard and optional features, the Drive provides the lowest overall cost of ownership.

[← BACK TO CONFIGURATION](#) [← RETURN TO: CONFIGURATOR HOME](#)

- General Information
- Configuration Details**
- Efficiency Data
- DrivePro®
- Documents
- Accessories
- Services

CHARACTERISTIC	VALUE
Product Group	(FC-) VLT® HVAC Drive FC-
Series	102
Power Rating	(P15K) 15 KW / 20 HP
Phase	(T) Three phase
Mains Voltage	(4) 380 - 480 VAC
Enclosure	(P55) IP55 / Type12 Backplate
RFI Filter	(H1) RFI Class A1/B (C1)
Brake - Safe Stop	(X) No brake chopper
LCP	(G) Graphical Loc. Cont. Panel
Coating PCB	(X) Not coated PCB
Mains Option	(X) No Mains Option
Adaptation A	(X) Standard Cable Entries
Adaptation B	(X) No adaptation
Software Release	(SXXX) Latest release std. SW.
Software Language Pack	(X) Standard Language Pack
A Option	(AX) No A Option
B Option	(BX) No B Option
C0 Option MCO	(CX) No C0 option
C1 Option	(X) No C1 option
C Option Software	(XX) No software option
D Option	(DX) No D option
Frame Size	B1
Product Catalog	Global (Standard)
Typecode Part 1	FC-102P15KT4P55H1XGX
Typecode Part 2	XXXXXXXAXBXCXXXXDX
Power 110% (NO) [KW]	15
Height [mm]	480,0
Width w/ no C options [mm]	242,0
Depth [mm]	260,0
Depth with Option A/B [mm]	260,0
kVA	22.2

Power Loss NO [W]	392
Continuous Current (NO) [A]	32
Intermittent Current (NO) [A]	35.2
Continuous Current (NO) [A]	27
Intermittent Current (NO) [A]	29.7
Calculated Gross Weight	23.500
Calculated Net Weight [kg]	23.200
Vendor	Cannot Determine Vendor
Modelcode01	FC-102P15KT4P55H1XGX
Modelcode02	XXSXXXXAXBXXXXDX