

NULL

**PRODUCT DETAILS - 131B4218****VLT® HVAC DRIVE FC 102**

Danfoss VLT® HVAC Drive FC-102 Drive is dedicated to ventilation, heating, and refrigeration applications. With a wide range of powerful standard and optional features, the Drive provides the lowest overall cost of ownership.

CONFIGURATION DETAILS

CHARACTERISTIC	VALUE
PRODUCT GROUP	(FC-) VLT® HVAC Drive FC-
SERIES	102
POWER RATING	(P2K2) 2.2 KW / 3.0 HP
PHASE	(T) Three phase
MAINS VOLTAGE	(4) 380 - 480 VAC
ENCLOSURE	(E20) IP20 / Chassis
RFI FILTER	(H1) RFI Class A1/B (C1)
BRAKE - SAFE STOP	(X) No brake chopper
LCP	(G) Graphical Loc. Cont. Panel
COATING PCB	(X) Not coated PCB
MAINS OPTION	(X) No Mains Option
ADAPTATION A	(X) Standard Cable Entries
ADAPTATION B	(X) No adaptation
SOFTWARE RELEASE	(SXXX) Latest release std. SW.
SOFTWARE LANGUAGE PACK	(X) Standard Language Pack
A OPTION	(AX) No A Option
B OPTION	(BX) No B Option
C0 OPTION MCO	(CX) No C0 option
C1 OPTION	(X) No C1 option
C OPTION SOFTWARE	(XX) No software option
D OPTION	(DX) No D option
FRAME SIZE	A2
PRODUCT CATALOG	Global (Standard)

EXTRAS

> [Display General Information](#)

> [Display Configuration](#)

> [DrivePro® Services & Parts](#)

> [Display Power Options](#)

> [Display Documents](#)

> [Display Accessories](#)

> [Display Services](#)

TYPECODE PART 1	FC-102P2K2T4E20H1XGX
TYPECODE PART 2	XXXSXXXAXBXCXXXDX
POWER 110% (NO) [KW]	2.2
HEIGHT [MM]	268,0
WIDTH W/ NO C OPTIONS [MM]	90,0
DEPTH [MM]	205,0
DEPTH WITH OPTION A/B [MM]	220,0
KVA	3.88
POWER LOSS NO [W]	88
POWER LOSS NO [W]	88
CONTINUOUS CURRENT (NO) [A]	5.6
INTERMITTENT CURRENT (NO) [A]	6.16
CONTINUOUS CURRENT (NO) [A]	4.8
INTERMITTENT CURRENT (NO) [A]	5.28
MATERIAL GROSS WEIGHT	5.055
MATERIAL NET WEIGHT	4.900
VENDOR	Factory DK