

PRODUCT
VLT® HVAC DRIVE FC 102

STATUS
COMPLETE

RESET CONFIGURATION CANCEL

Configure by Nomenclature Code or Material Number

CONFIGURE

CONFIGURATION HAS CHANGED.



| | | |
|-------------------------------|--------------------------------|---------------------|
| Product Group | (FC-) VLT® HVAC Drive FC- | Display all Options |
| Series | (102) 102 | Display all Options |
| Power Rating | (P5K5) 5.5 KW / 7.5 HP | Display all Options |
| Phase | (T) Three phase | Display all Options |
| Mains Voltage | (4) 380 -480 VAC | Display all Options |
| Enclosure | (P55) IP55 / Type12 Backplate | Display all Options |
| RFI Filter | (H1) RFI Class A1/B (C1) | Display all Options |
| Brake - Safe Stop | (X) No brake chopper | Display all Options |
| LCP | (G) Graphical Loc. Cont. Panel | Display all Options |
| Coating PCB | (X) Not coated PCB | Display all Options |
| Mains Option | (X) No Mains Option | Display all Options |
| Adaptation A | (X) Standard Cable Entries | Display all Options |
| Adaptation B | (X) No adaptation | Display all Options |
| Software Release | (SXXX) Latest release std. SW. | Display all Options |
| Software Language Pack | (X) Standard Language Pack | Display all Options |
| A Option | (AX) No A Option | Display all Options |
| B Option | (BX) No B Option | Display all Options |
| C0 Option MCO | (CX) No C0 option | Display all Options |
| C1 Option | (X) No C1 option | Display all Options |
| C Option Software | (XX) No software option | Display all Options |
| D Option | (DX) No D option | Display all Options |
| Frame Size | (A5) A5 | Display all Options |
| Product Catalog | (GLBL) Global (Standard) | Display all Options |
| Typecode Part 1 | FC-102P5K5T4P55H1XGX | |
| Typecode Part 2 | XXXXXXXAXBXXXXDX | |
| Power 110% (NO) [KW] | 5.5 | |
| Height [mm] | 420,0 | |
| Width w/ no C options | 212,0 | |

PRODUCT
VLT® HVAC DRIVE FC 102

MODEL CODE

FC-102P5K5T4P55H1XGXXXXSXXXXAXBXXXXDX

| | | |
|--------------------------------------|---------------------------------|-------------------------------------|
| Depth [mm] | 200,0 | |
| Depth with Option A/B [mm] | 200,0 | |
| kVA | 9.01 | |
| Power Loss NO [W] | 187 | |
| Power Loss NO [W] | 187 | |
| Continuous Current (NO) [A] | 13 | |
| Intermittent Current (NO) [A] | 14.3 | |
| Continuous Current (NO) [A] | 11 | |
| Intermittent Current (NO) [A] | 12.1 | |
| Calculated Gross Weight | 15.300 | |
| Calculated Net Weight [kg] | 15.000 | |
| Vendor | (ERR01) Cannot Determine Vendor | Display all Options |
| Modelcode01 | FC-102P5K5T4P55H1XGX | |
| Modelcode02 | XXSXXXAXBXXXXDX | |

 [ACCEPT](#)