

NULL

**PRODUCT DETAILS – 131F6768****VLT® AQUA DRIVE FC 202**

Danfoss VLT® AQUA Drive is dedicated to water and wastewater applications. With a wide range of powerful standard and optional features, the VLT® AQUA Drive provides the lowest overall cost of ownership for water and wastewater applications.

CONFIGURATION DETAILS

CHARACTERISTIC	VALUE
PRODUCT GROUP	(FC-) VLT® AQUA Drive FC-
SERIES	202
POWER RATING	(P22K) 22 KW / 30 HP
PHASE	(T) Three phase
MAINS VOLTAGE	(4) 380 - 480 VAC
ENCLOSURE	(E20) IP20 / Chassis
RFI FILTER	(H1) RFI Class A1/B (C1)
BRAKE - SAFE STOP	(X) No brake chopper
LCP	(G) Graphical Loc. Cont. Panel
COATING PCB	(X) Not coated PCB
MAINS OPTION	(X) No Mains Option
ADAPTATION A	(X) Standard Cable Entries
ADAPTATION B	(X) No adaptation
SOFTWARE RELEASE	(SXXX) Latest release std. SW.
SOFTWARE LANGUAGE PACK	(X) Standard Language Pack
A OPTION	(AX) No A Option
B OPTION	(BX) No B Option
C0 OPTION MCO	(CX) No C0 option
C1 OPTION	(X) No C1 option
C OPTION SOFTWARE	(XX) No software option
D OPTION	(DX) No D option
FRAME SIZE	B4
TYPECODE PART 1	FC-202P22KT4E20H1XGX

EXTRAS

> [Display General Information](#)

> [Display Configuration](#)

> [DrivePro® Services & Parts](#)

> [Display Power Options](#)

> [Display Documents](#)

> [Display Accessories](#)

> [Display Services](#)

TYPECODE PART 2	XXXSXXXXAXBXXXXDX
PRODUCT CATALOG	Global (Standard)
MATERIAL GROSS WEIGHT	20.182
MATERIAL NET WEIGHT	19.882
VENDOR	Factory DK