



PRODUCT DETAILS – 131F6773 / EAN: 5702427466760

VLT® AQUA DRIVE FC 202

FC-202P30KT4E20H1XGXXXXSXXXXAXBXXXXDX

Danfoss VLT® AQUA Drive is dedicated to water and wastewater applications. With a wide range of powerful standard and optional features, the VLT® AQUA Drive provides the lowest overall cost of ownership for water and wastewater applications.

Productdata
 VLT® AQUA Drive FC-
 30 KW / 40 HP, 380 - 480 VAC, No brake chopper, IP20 / Chassis,
 RFI Class A1/B (C1),
 No A Option, No B Option, Not coated PCB, No Mains Option,
 FC-202P30KT4E20H1XGXXXXSXXXXAXBXXXXDX

[> Contact sales and service](#)

[← BACK TO CONFIGURATION](#) [← RETURN TO: CONFIGURATOR HOME](#)

General Information	Configuration Details	Efficiency Data	DrivePro®	Documents	Accessories	Services
CHARACTERISTIC	VALUE					
Product Group	(FC-) VLT® AQUA Drive FC-					
Series	202					
Power Rating	(P30K) 30 KW / 40 HP					
Phase	(T) Three phase					
Mains Voltage	(4) 380 - 480 VAC					
Enclosure	(E20) IP20 / Chassis					
RFI Filter	(H1) RFI Class A1/B (C1)					
Brake - Safe Stop	(X) No brake chopper					
LCP	(G) Graphical Loc. Cont. Panel					
Coating PCB	(X) Not coated PCB					
Mains Option	(X) No Mains Option					
Adaptation A	(X) Standard Cable Entries					
Adaptation B	(X) No adaptation					
Software Release	(SXXX) Latest release std. SW.					
Software Language Pack	(X) Standard Language Pack					
A Option	(AX) No A Option					
B Option	(BX) No B Option					
C0 Option MCO	(CX) No C0 option					
C1 Option	(X) No C1 option					
C Option Software	(XX) No software option					
D Option	(DX) No D option					
Frame Size	B4					
Typecode Part 1	FC-202P30KT4E20H1XGX					
Typecode Part 2	XXXSXXXXAXBXXXXDX					
Product Catalog	Global (Standard)					
Power 160% (HO) [KW]	22					
Power 110% (NO) [KW]	30					

Height [mm]	520,0
Width w/ no C options [mm]	230,0
Depth [mm]	242,0
Depth with Option A/B [mm]	242,0
kVA	42.3
Power Loss NO [W]	739
Power Loss NO [W]	739
Power Loss HO [W]	547
Power Loss HO [W]	547
Continuous Current (NO) [A]	61
Intermittent Current (NO) [A]	67.1
Continuous Current (NO) [A]	52
Intermittent Current (NO) [A]	57.2
Continuous Current (HO) [A]	44
Intermittent Current (HO) [A]	70.4
Continuous Current (HO) [A]	40
Intermittent Current (HO) [A]	64
Calculated Gross Weight	23.800
Calculated Net Weight [kg]	23.500
Vendor	Cannot Determine Vendor