

NULL

**PRODUCT DETAILS – 131U5997****VLT® AUTOMATIONDRIVE FC 300**

The VLT® AutomationDrive represents a single drive concept that controls the entire range of operations from ordinary to servo like applications on any machine or production line.

CONFIGURATION DETAILS

CHARACTERISTIC	VALUE
PRODUCT GROUP	(FC-) VLT® AutomationDrive FC-
SERIES	302
POWER RATING	(P4K0) 4.0 KW / 5.5 HP
PHASE	(T) Three phase
MAINS VOLTAGE	(5) 380 - 500 VAC
ENCLOSURE	(Y55) IP55 / Type 12 Backplate
RFI FILTER	(H1) RFI Class A1/B (C1)
BRAKE - SAFE STOP	(X) No brake chopper
LCP	(G) Graphical Loc. Cont. Panel
COATING PCB	(X) Not coated PCB
MAINS OPTION	(X) No Mains Option
ADAPTATION A	(X) Standard Cable Entries
ADAPTATION B	(X) No adaptation
SOFTWARE RELEASE	(SXXX) Latest release std. SW.
SOFTWARE LANGUAGE PACK	(X) Standard Language Pack
A OPTION	(AX) No A Option
B OPTION	(BX) No B Option
C0 OPTION MCO	(CX) No C0 option
C1 OPTION	(X) No C1 option
C OPTION SOFTWARE	(XX) No software option
D OPTION	(DX) No D option
FRAME SIZE	A4
TYPECODE PART 1	FC-302P4K0T5Y55H1XGX

EXTRAS

> [Display General Information](#)

> [Display Configuration](#)

> [DrivePro® Services & Parts](#)

> [Display Power Options](#)

> [Display Documents](#)

> [Display Accessories](#)

> [Display Services](#)

TYPECODE PART 2	XXXXXXXXAXBXXXXDX
PRODUCT CATALOG	Global (Standard)
POWER 160% (HO) [KW]	4
HEIGHT [MM]	390,0
WIDTH W/ NO C OPTIONS [MM]	200,0
DEPTH [MM]	175,0
DEPTH WITH OPTION A/B [MM]	175,0
KVA	6.93
POWER LOSS HO [W]	124
POWER LOSS HO [W]	124
CONTINUOUS CURRENT (HO) [A]	10
INTERMITTENT CURRENT (HO) [A]	16
CONTINUOUS CURRENT (HO) [A]	8.2
INTERMITTENT CURRENT (HO) [A]	13.1
MATERIAL GROSS WEIGHT	9.600
MATERIAL NET WEIGHT	8.000
VENDOR	Factory DK