



PRODUCT DETAILS – 136G7336 / EAN: 5710108637996

VLT® SOFT STARTER MCD 600

MCD60020BT5S1X20CV1

VLT® Soft Starter MCD 600 is a total motor starting solution.

Current transformers measure motor current and provide feedback for controlled motor ramp profiles.

Adaptive Acceleration Control (AAC) automatically employs the best starting and stopping profile for the application. Emergency mode and Pump clean function are standard features.

The optional remote control panel adds more functionality, such as the Start/Stop buttons, and quick jump buttons to menu options.

VLT® Soft Starter MCD 600 is available in three enclosure sizes:

S1, S2 and S3

S1: IP20 with built-in bypass contactor (20–129 A)

S2: IP00 either with built-in bypass or non-bypass (144–579 A).

S3: IP00 with built-in bypass, non-bypass or external bypass (590–1250 A)

To achieve protection rating IP20 on connections, order the Finger Guard Kit as an accessory.

[← BACK TO CONFIGURATION](#)

[← RETURN TO: CONFIGURATOR HOME](#)

General Information

Configuration Details

DrivePro®

Documents

Accessories

Services

Code No.	136G7336
Product	VLT® Soft Starter MCD 600
Modelcode	MCD60020BT5S1X20CV1
	VLT® Soft Starter MCD 600
	With Int. Bypass Contactor
	20 A, Three phase 200-525 V AC
	Frame size 1, IP20
	Control Voltage: 24 VAC/VDC
	Other options according to:
	MCD60020BT5S1X20CV1
EAN	5710108637996