



130B1110 🗷

VLT® Relay Option MCB 105, uncoated

Relay extension for FC 100 and FC 300. Extension with 3 additional load relays (changeover contacts), easy to retrofit thanks to modular technology.

Max. Load 240V AC (resistive): 2 A Max. Load 240V AC (Cos Phi 0.4): 0.2 A Max. Load 24V DC (ohmic): 1 A

Max. Load 24V DC (inductive): 0.1 A

PRODUCT DETAILS

| Gross weight | | 0.734 kg | |
|-----------------------|------|------------------|--|
| Net weight | | 0.521 kg | |
| Volume | | 01 | |
| EAN | | 5702427153202 | |
| ACCESSORIES FC 100 SE | RIES | | |
| B Option | BX | (BX) No B Option | |
| ACCESSORIES FC 103 SE | RIES | | |
| /B Option | ВХ | (BX) No B Option | |
| ACCESSORIES FC 300 SE | RIES | | |
| B Option | BX | (BX) No B Option | |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store $\[mathbb{L}\]$

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.