



060G1105 🗷

Pressure transmitter, MBS 3000, 0.00 bar - 40.00 bar, 0.00 psi - 580.15 psi
Output signal: Current, Electrical connection: DIN-plug, Pressure connection
type: G, Pressure connection size: 1/4, Specification key: MBS
3000-2631-A1AB04-0

PRODUCT DETAILS

| Gross weight | 0.17 kg |
|--------------------------------|----------------------|
| Net weight | 0.15 kg |
| EAN | 5702423057627 |
| + supply | Pin 1 |
| - common | Pin 2 |
| Accuracy, max. +/- FS [%] | 1 % |
| Accuracy, typical +/- FS [%] | 0.5 % |
| Adj. zero point and span | No |
| Ambient temperature range [°C] | 85 °C |
| [Max] | |
| Ambient temperature range [°C] | -40 °C |
| [Min] | |
| Ambient temperature range [°F] | 185 °F |
| [Max] | |
| Ambient temperature range [°F] | -40 °F |
| [Min] | |
| Approval | ATEX |
| Approval comments | ATEX Ex ec IIA T4 Gc |
| Compensated temp. range [°C] | 80 ℃ |
| [Max] | |
| Compensated temp. range [°C] | 0 ℃ |
| [Min] | |
| Compensated temp. range [°F] | 176 °F |
| [Max] | |
| Compensated temp. range [°F] | 32 °F |
| [Min] | |
| Electrical conn. Male/Female | Male and Female |
| Electrical connection | DIN-plug |
| Electrical connection size | Pg 9 |
| Electrical connection standard | EN 175301-803-A |
| Enclosure rating IP | IP65 |
| Flush diaphragm | No |
| High Clipping Level | 22.4 |
| International Article Number | 5702423057627 |
| Intrinsically safe | No |
| Low Clipping Level | 3.6 |
| Medium temperature range [°C] | 85 °C |
| [Max] | |
| | |

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



| PRODUCT DETAILS | |
|---------------------------------|------------------------------------|
| Medium temperature range [°C] | -40 °C |
| [Min] | |
| Medium temperature range [°F] | 185 °F |
| [Max] | |
| Medium temperature range [°F] | -40 °F |
| [Min] | |
| Non-linearity BFSL ±FS [%] | 0.5 % |
| Output signal | Current |
| Output signal [mA] [Max] | 20 mA |
| Output signal [mA] [Min] | 4 mA |
| Overload pressure max. [bar] | 240 bar |
| Overload pressure max. [psi] | 3481 psi |
| Packing format | Multi pack |
| Pressure connection HEX [mm] | 27 mm |
| Pressure connection size | 1/4 |
| Pressure connection standard | EN 837 |
| Pressure connection type | G |
| Pressure Male/Female | Male |
| Pressure range [bar] [Max] | 40 bar |
| Pressure range [bar] [Min] | 0 bar |
| Pressure range [psi] [Max] | 580.15 psi |
| Pressure range [psi] [Min] | 0 psi |
| Pressure reference | Sealed gauge |
| Product Group | Sensors |
| Product name | Pressure transmitter |
| Pulse-snubber | No |
| Quantity per packing format | 14 pc |
| REACH Candidate List substances | Lead (CAS no. 7439-92-1) |
| >0.1% | Dodecamethylcyclohexasiloxane (D6, |
| | CAS no. 540-97-6) |
| Response time max. [ms] | 4 ms |
| Specification key | MBS 3000-2631-A1AB04-0 |
| Supply voltage [V] DC [Max] | 32 V |
| Supply voltage [V] DC [Min] | 9 V |

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store $\[mathbb{L}\]$

MBS 3000

Accessories

Type



060G0008 ≥

Plug, Plug

Further information: Knife Contacts, Used for product: AKS/MBS, Packing format: Multi pack, Quantity per packing format: 96

For more information, please use this link to visit the product page on Danfoss Product Store 🗅

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



Accessories



060G1034 @

Accessories, sensors, Accessory Plug Connector 5m Cable

Accessory Plug Connector 5m Cable, Used for product: AKS/MBS, Packing format: Multi pack, Quantity per packing format: 8



060G2850 ≥

Accessory MBD 1000 Display MBT/MBS/AKS

Accessory MBD 1000 Display MBT/MBS/AKS