



#### 060G1430 🗷

Pressure transmitter, MBS 3000, 0.00 bar - 25.00 bar, 0.00 psi - 362.59 psi Pressure reference: Gauge (relative), Output signal: Current, Electrical connection: DIN-plug, Pressure connection type: G, Pressure connection size: 1/4, Specification key: MBS 3000-2411-A1AB04-0

#### PRODUCT DETAILS

Gross weight	0.17 kg
Net weight	0.15 kg
EAN	5702423110728
+ supply	Pin 1
- common	Pin 2
Accuracy, max. +/- FS [%]	1 %
Accuracy, typical +/- FS [%]	0.5 %
Adj. zero point and span	No
Ambient temperature range [°C]	85 °C
[Max]	
Ambient temperature range [°C]	-40 °C
[Min]	
Ambient temperature range [°F]	185 °F
[Max]	
Ambient temperature range [°F]	-40 °F
[Min]	
Approval	ATEX
Approval comments	ATEX Ex ec IIA T4 Gc
Compensated temp. range [°C]	80 °C
[Max]	
Compensated temp. range [°C]	0 ℃
[Min]	
Compensated temp. range [°F]	176 °F
[Max]	
Compensated temp. range [°F]	32 °F
[Min]	
Electrical conn. Male/Female	Male and Female
Electrical connection	DIN-plug
Electrical connection size	Pg 9
Electrical connection standard	EN 175301-803-A
Enclosure rating IP	IP65
Flush diaphragm	No
High Clipping Level	22.4
International Article Number	5702423110728
Intrinsically safe	No
Low Clipping Level	3.6
Medium temperature range [°C]	85 ℃
[Max]	

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



PRODUCT DETAILS	
Medium temperature range [°C]	-40 °C
[Min]	
Medium temperature range [°F]	185 °F
[Max]	
Medium temperature range [°F]	-40 °F
[Min]	
Non-linearity BFSL ±FS [%]	0.5 %
Output signal	Current
Output signal [mA] [Max]	20 mA
Output signal [mA] [Min]	4 mA
Overload pressure max. [bar]	150 bar
Overload pressure max. [psi]	2176 psi
Packing format	Multi pack
Pressure connection HEX [mm]	27 mm
Pressure connection size	1/4
Pressure connection standard	EN 837
Pressure connection type	G
Pressure Male/Female	Male
Pressure range [bar] [Max]	25 bar
Pressure range [bar] [Min]	0 bar
Pressure range [psi] [Max]	362.59 psi
Pressure range [psi] [Min]	0 psi
Pressure reference	Gauge (relative)
Product Group	Sensors
Product name	Pressure transmitter
Pulse-snubber	No
Quantity per packing format	14 pc
REACH Candidate List substances	Lead (CAS no. 7439-92-1)
>0.1%	Dodecamethylcyclohexasiloxane (D6,
	CAS no. 540-97-6)
Response time max. [ms]	4 ms
Specification key	MBS 3000-2411-A1AB04-0
Supply voltage [V] DC [Max]	32 V
Supply voltage [V] DC [Min]	9 V

For Documents, Software, Visuals and more information, please use this link to visit the product page on Danfoss Product Store  $\@ifnextchar[{\@model{L}}{\@model{L}}$ 

MBS 3000

## Accessories

Type



# 060G0008 ≥

Plug, Plug

Further information: Knife Contacts, Used for product: AKS/MBS, Packing format: Multi pack, Quantity per packing format: 96

#### For more information, please use this link to visit the product page on Danfoss Product Store 🗅

Danfoss can accept no responsibility for possible errors in catalogs, brochures and other printed material. Danfoss reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without sub-sequential changes being necessary in specifications already agreed. All trademarks in this material are property of the respective companies. Danfoss and the Danfoss logotype are trademarks of Danfoss A/S. All rights reserved.



#### Accessories



## 060G1034 @

#### Accessories, sensors, Accessory Plug Connector 5m Cable

Accessory Plug Connector 5m Cable, Used for product: AKS/MBS, Packing format: Multi pack, Quantity per packing format: 8

# 060G2850 ⊡



Accessory MBD 1000 Display MBT/MBS/AKS
Accessory MBD 1000 Display MBT/MBS/AKS

For more information, please use this link to visit the product page on Danfoss Product Store 🗅