

**TS 15X5/LL 2M/ST/ZN****Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

**Product image**

Steel DIN rails are the most widespread on the market. Among metal DIN rails, they have the lowest shortcircuit protection, similar to stainless steel.

**General ordering data**

Version	Rail, TS 15, with slot, Steel, galvanic zinc plated and passivated
Order No.	<a href="#">0117500000</a>
Type	TS 15X5/LL 2M/ST/ZN
GTIN (EAN)	4008 190150662
Qty.	2 m

Creation date 01 February 2022 03:11:37 CET

Catalogue status 14.01.2022 / We reserve the right to make technical changes.

## TS 15X5/LL 2M/ST/ZN

**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

## Technical data

### Dimensions and weights

Depth	5.5 mm	Depth (inches)	0.217 inch
Height	15 mm	Height (inches)	0.591 inch
Width	2,000 mm	Width (inches)	78.74 inch
Net weight	140 g		

### Mounting rail

Drill-hole diameter	4.2 mm	
Installation advice	Direct mounting	
Length of the terminal rail	nominal	2,000 mm
	max.	2,000 mm
	min.	0 mm
Material	Steel	
Pre-punched mounting rail	Yes	
Short circuit strength corresponds to E-Cu wire	10 mm <sup>2</sup>	
Short-time withstand current according to IEC 60947-7-2	1.2 kA/1s	
Slit gap	8 mm	
Slit gap		
Slit length	12 mm	
Slit length		
Slit width	4.2 mm	
Slit width		
Slotted drill holes	Yes	
Solder eyelet hole diameter (D)	4.2 mm	
Spacing of holes, centre-to-centre	20 mm	
Standards	DIN EN 60715	
Surface finish	galvanic zinc plated and passivated	
Thickness	1 mm	

### Classifications

ETIM 6.0	EC001285	ETIM 7.0	EC001285
ETIM 8.0	EC001285	ECLASS 9.0	27-40-06-02
ECLASS 9.1	27-40-06-02	ECLASS 10.0	27-40-06-02
ECLASS 11.0	27-40-06-02		

### Approvals

ROHS	Conform
------	---------

### Downloads

Engineering Data	<a href="#">CAD data – STEP</a>
Engineering Data	<a href="#">EPLAN, WSCAD, Zuken E3.S</a>
User Documentation	<a href="#">StorageConditionsTerminalBlocks</a>
Catalogues	<a href="#">Catalogues in PDF-format</a>
Brochures	