

CP DC UPS TF25

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com



Due to the wide range of variants with output voltages of 5, 12, 24, and 48 V and extensive international approvals, they are suitable for use in many applications. The power range extends from 35 W to 350 W. The individual adaptability makes PRO-PM the right choice for many standard machines.

General ordering data

Version	
Order No.	1444540000
Type	CP DC UPS TF25
GTIN (EAN)	4050118249880
Qty.	1 pc(s).

Creation date 07 February 2022 04:47:09 CET

Catalogue status 03.02.2022 / We reserve the right to make technical changes.

CP DC UPS TF25

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

Net weight 142 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Classifications

ETIM 6.0	EC001578	ETIM 7.0	EC003250
ETIM 8.0	EC003250	ECLASS 9.0	27-06-20-11
ECLASS 9.1	27-06-90-90	ECLASS 10.0	27-06-01-06
ECLASS 11.0	27-06-01-06		

Approvals

Approvals



ROHS Conform

Downloads

User Documentation	Operating instruction
Catalogues	Catalogues in PDF-format