

A4C 4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Product image**Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

| | |
|------------|---|
| Version | Feed-through terminal, PUSH IN, 4 mm ² , 800 V, 32 A, dark beige |
| Order No. | 2051500000 |
| Type | A4C 4 |
| GTIN (EAN) | 4050118411621 |
| Qty. | 50 pc(s). |

Creation date 08 February 2022 03:02:26 CET

Catalogue status 03.02.2022 / We reserve the right to make technical changes.

A4C 4**Weidmüller Interface GmbH & Co. KG**

Klingenbergstraße 26

D-32758 Detmold

Germany

www.weidmueller.com

Technical data**Dimensions and weights**

| | | | |
|--------------------------|------------|----------------|------------|
| Depth | 39.5 mm | Depth (inches) | 1.555 inch |
| Depth including DIN rail | 40.5 mm | Height | 87.5 mm |
| Height (inches) | 3.445 inch | Width | 6.1 mm |
| Width (inches) | 0.24 inch | Net weight | 15.06 g |

Temperatures

| | | | |
|----------------------------------|----------------|----------------------------------|--------|
| Storage temperature | -25 °C...55 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C | | |

Material data

| | | | |
|--------------------------------|--------|---------------------------|------------|
| Material | Wemid | Colour | dark beige |
| Colour of operational elements | orange | UL 94 flammability rating | V-0 |

Rating data IECEx/ATEX

| | | | |
|--------------------------------|-------------------|---------------------------------|-------------------|
| Certificate No. (ATEX) | TUEV16ATEX7909U | Certificate No. (IECEX) | IECEXTUR16.0036U |
| Max. voltage (ATEX) | 550 V | Current (ATEX) | 30 A |
| Wire cross section max. (ATEX) | 4 mm ² | Max. voltage (IECEX) | 550 V |
| Current (IECEX) | 30 A | Wire cross section max. (IECEX) | 4 mm ² |
| Marking EN 60079-7 | Ex eb II C Gb | Ex 2014/34/EU label | II 2 G D |

System specifications

| | | | |
|-------------------------------|-------|-------------------------------------|----|
| End cover plate required | Yes | Number of potentials | 1 |
| Number of levels | 1 | Number of clamping points per level | 4 |
| Number of potentials per tier | 1 | PE connection | No |
| Rail | TS 35 | N-function | No |
| PE function | No | PEN function | No |

Additional technical data

| | | | |
|---------------------|-------|-------------------|---------|
| Installation advice | Rail | Open sides | right |
| Snap-on | No | Type of fixing | Snap-on |
| Type of mounting | TS 35 | With snap-in pegs | No |

CSA rating data

| | | | |
|-------------------------------|-----------------|-------------------------------|--------|
| Certificate No. (CSA) | 200039-70089609 | Current size B (CSA) | 30 A |
| Current size C (CSA) | 30 A | Current size D (CSA) | 5 A |
| Voltage size B (CSA) | 600 V | Voltage size C (CSA) | 600 V |
| Voltage size D (CSA) | 600 V | Wire cross section max. (CSA) | 10 AWG |
| Wire cross section min. (CSA) | 26 AWG | | |

Conductors for clamping (rated connection)

| | |
|--|----------------------|
| Blade size | 0.6 x 3.5 mm |
| Clamping range, max. | 4 mm ² |
| Clamping range, min. | 0.14 mm ² |
| Connection cross-section, stranded, max. | 4 mm ² |
| Connection cross-section, stranded, min. | 0.5 mm ² |
| Connection direction | top |
| Gauge to IEC 60947-1 | A4 |

Creation date 08 February 2022 03:02:26 CET

A4C 4

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

| | | | | |
|---|---|------------------------------|---------------------|-------|
| Number of connections | 4 | | | |
| Stripping length | 12 mm | | | |
| Tube length for twin wire-end ferrule | Cross-section for conductor connection | min. | 0.5 mm ² | |
| | | max. | 1.5 mm ² | |
| | Tube length | max. | 12 mm | |
| | | min. | 8 mm | |
| Tube length for wire-end ferrule with plastic collar DIN 46228/4 | Cross-section for conductor connection | min. | 0.5 mm ² | |
| | | max. | 1 mm ² | |
| | Tube length | max. | 12 mm | |
| | | min. | 6 mm | |
| | Cross-section for conductor connection | min. | 1.5 mm ² | |
| | | max. | 2.5 mm ² | |
| | Tube length | max. | 12 mm | |
| | | min. | 8 mm | |
| | Cross-section for conductor connection | nominal | 4 mm ² | |
| | | Tube length | max. | 12 mm |
| | Tube length for wire-end ferrule without plastic collar DIN 46228/1 | Tube length | max. | 10 mm |
| | | | min. | 6 mm |
| Cross-section for conductor connection | | min. | 0.5 mm ² | |
| | | max. | 1 mm ² | |
| Tube length | | max. | 12 mm | |
| | | min. | 7 mm | |
| Cross-section for conductor connection | | min. | 1.5 mm ² | |
| | | max. | 2.5 mm ² | |
| Tube length | | max. | 15 mm | |
| | | min. | 9 mm | |
| Cross-section for conductor connection | | nominal | 4 mm ² | |
| | | Twin wire-end ferrules, max. | 1.5 mm ² | |
| Twin wire-end ferrules, min. | 0.5 mm ² | | | |
| Type of connection | PUSH IN | | | |
| Wire connection cross section AWG, max. | AWG 12 | | | |
| Wire connection cross section AWG, min. | AWG 26 | | | |
| Wire connection cross section, finely stranded, max. | 4 mm ² | | | |
| Wire connection cross section, finely stranded, min. | 0.5 mm ² | | | |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 4 mm ² | | | |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 0.5 mm ² | | | |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 4 mm ² | | | |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.5 mm ² | | | |
| Wire connection cross-section, solid core, max. | 4 mm ² | | | |
| Wire connection cross-section, solid core, min. | 0.5 mm ² | | | |

A4C 4

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

General

| | | | |
|---|---------------|---|--------|
| Installation advice | Rail | Rail | TS 35 |
| Standards | IEC 60947-7-1 | Wire connection cross section AWG, max. | AWG 12 |
| Wire connection cross section AWG, min. | AWG 26 | | |

Rating data

| | | | |
|---------------------------------|-------------------|--|--------|
| Rated cross-section | 4 mm ² | Rated voltage | 800 V |
| Rated current | 32 A | Current at maximum wires | 32 A |
| Standards | IEC 60947-7-1 | Volume resistance according to IEC 60947-7-x | 1 mΩ |
| Rated impulse withstand voltage | 8 kV | Power loss in accordance with IEC 60947-7-x | 1.02 W |
| Pollution severity | 3 | Surge voltage category | III |

UL rating data

| | | | |
|--|--------|--|--------|
| Certificate No. (cURus) | E60693 | Conductor size Factory wiring max. (cURus) | 10 AWG |
| Conductor size Factory wiring min. (cURus) | 28 AWG | Conductor size Field wiring max. (cURus) | 10 AWG |
| Conductor size Field wiring min. (cURus) | 28 AWG | Current size B (cURus) | 30 A |
| Current size C (cURus) | 30 A | Current size D (cURus) | 5 A |
| Voltage size B (cURus) | 600 V | Voltage size C (cURus) | 600 V |
| Voltage size D (cURus) | 600 V | | |

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000897 | ETIM 7.0 | EC000897 |
| ETIM 8.0 | EC000897 | ECLASS 9.0 | 27-14-11-20 |
| ECLASS 9.1 | 27-14-11-20 | ECLASS 10.0 | 27-14-11-20 |
| ECLASS 11.0 | 27-14-11-20 | | |

Approvals

Approvals



| | |
|-----------------------|---------|
| ROHS | Conform |
| UL File Number Search | E60693 |

A4C 4

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data

Downloads

| | |
|---|---|
| Approval/Certificate/Document of Conformity | Attestation of Conformity IECEX Certificate ATEX Certificate CB Test Certificate CB Certificate EAC certificate DNVGL certificate BV certificate MARITREG certificate CCC Ex Certificate CE Declaration of Conformity CE Declaration of Conformity all terminals |
| Engineering Data | CAD data – STEP |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Tender specification | Klippon® Connect 205 1500000 DE Klippon® Connect 205 1500000 EN |
| User Documentation | NTI_A4C 4.pdf StorageConditionsTerminalBlocks NTI ALO 16 BPZL AXC 1.5-16 |
| Catalogues | Catalogues in PDF-format |
| Brochures | |

Data sheet

A4C 4

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Drawings

