

WQB B/4

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Product image



General ordering data

| | |
|------------|---|
| Version | W-Series, Cross-connector, For the terminals, Number of poles: 4 |
| Order No. | 1579030000 |
| Type | WQB B/4 |
| GTIN (EAN) | 4008 190185046 |
| Qty. | 50 pc(s). |

Creation date January 30, 2023 2:46:02 AM CET

Catalogue status 24.01.2023 / We reserve the right to make technical changes.

WQB B/4

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany

www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|----------|-----------------|------------|
| Depth | 2.5 mm | Depth (inches) | 0.098 inch |
| Height | 23.5 mm | Height (inches) | 0.925 inch |
| Width | 20.42 mm | Width (inches) | 0.804 inch |
| Net weight | 1.3 g | | |

Temperatures

| | | | |
|---------------------|----------------|----------------------------------|-------|
| Storage temperature | -25 °C...55 °C | Continuous operating temp., max. | 70 °C |
|---------------------|----------------|----------------------------------|-------|

Material data

| | | | |
|----------|---------------|--------|-------|
| Material | tinned copper | Colour | black |
|----------|---------------|--------|-------|

System specifications

| | |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

Additional technical data

| | | | |
|--------------------------|-----------------|---------------------|-----------------|
| Explosion-tested version | No | Installation advice | Direct mounting |
| Type of fixing | when screwed in | | |

Cross-connector

| | | | |
|-------------------------------------|-----------------|---------------------------|------|
| Number of cross-connected terminals | 4 | Rated current, multi-pole | 24 A |
| Type | Cross-connector | | |

Dimensions

| | |
|-----------------|--------|
| Pitch in mm (P) | 5.1 mm |
|-----------------|--------|

General

| | | | |
|---------------------|-----------------|-----------------|---|
| Installation advice | Direct mounting | Number of poles | 4 |
|---------------------|-----------------|-----------------|---|

Rating data

| | |
|---------------|-----|
| Rated voltage | 800 |
|---------------|-----|

Classifications

| | | | |
|-------------|-------------|-------------|-------------|
| ETIM 6.0 | EC000489 | ETIM 7.0 | EC000489 |
| ETIM 8.0 | EC000489 | ECLASS 9.0 | 27-14-11-40 |
| ECLASS 9.1 | 27-14-11-40 | ECLASS 10.0 | 27-14-11-40 |
| ECLASS 11.0 | 27-14-11-40 | ECLASS 12.0 | 27-14-11-40 |

Approvals

Approvals



| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Creation date January 30, 2023 2:46:02 AM CET

Catalogue status 24.01.2023 / We reserve the right to make technical changes.

WQB B/4

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany

www.weidmueller.com

Technical data**Downloads**

| | |
|---|---|
| Approval/Certificate/Document of Conformity | EAC certificate |
| Engineering Data | CAD data – STEP |
| Engineering Data | WSCAD, Zuken E3.S |
| User Documentation | StorageConditionsTerminalBlocks |
| Catalogues | Catalogues in PDF-format |
